



Features

- Complies with 802.11ac/a/b/g/n standards.
- 300Mbps on 2.4GHz and 867Mbps on 5GHz band simultaneously.
- Four fixed high gain antennas with advanced MIMO technology.
- Supports DHCP, Static IP, PPPoE(dual access), PPTP(dual access), L2TP(dual access) broadband functions.
- Provides 64/128-bit WEP, WPA, WPA2 and WPA/WPA2 (TKIP+AES) security.
- Connects to secure network easily and fast using WPS.
- QoS: Bandwidth Control based on IP/MAC.
- Supports IP, MAC, URL filtering and Port Forwarding.
- Universal Repeater and WDS function for easy Wi-Fi extension.
- Multi-SSID allows users to create multiple Wi-Fi networks.
- Supports easy and fast IPTV settings.
- Easy setup with auto popup window simplifies the basic settings.

Specifications

Hardware		
Interface	- 4 *100Mbps LAN Ports - 1 *100Mbps WAN Port	
Power Supply	- 9V DC/0.8A	
Chipset	- Realtek8197DL+8192ER+8812AR	
Flash/SDROM	- 8M/64M	
Antenna	- 2 *5dBi fixed antennas (2.4G), 2 *5dBi fixed antennas (5G)	
Button	- 1 *RST Button - 1 *WPS Button	
LED Indicators	- 1 *Power, 1 *CPU, 1 *2.4G, 1 *5G, 1 *WAN, 4 *LAN	
Wireless		
Standards	- IEEE 802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b, IEEE 802.11a	
RF Frequency	- 2.4GHz/5GHz	
Data Rate	- 2.4GHz: Up to 300Mbps - 5GHz: Up to 867Mbps	
EIRP	- 2.4GHz < 20dBm	
	- 5GHz < 23dBm	
Wireless Security	- 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK (TKIP/AES)	
Reception Sensitivity	- 2.4G: 11b	

Software		
Operation Mode	- Wireless ISP Client Router - Wireless Client - Repeater(Range Extender) - Router - Bridge with AP - Client	
WAN Type	- DHCP/Static IP/PPPoE(dual access)/PPTP(dual access) /L2TP(dual access)	
IPv6 Network	- IPv6 WAN Setting - IPv6 LAN Setting - RADVD for IPv6 - IPv6 tunnel to IPv4	
Wireless Functions	- Multiple SSID, MAC Authentication, Universal Repeater, WDS, WPS, IPTV	
Schedule	- Reboot Schedule, Wireless Schedule	
Firewall	- MAC Filtering, IP Filtering, Port Filtering, URL Filtering,Port Forwarding, DMZ	
Management	- QoS, TR-069 config, DDNS, DoS, WMM, Access Control, etc.	
Others		
Package Contents	- A702R Wireless Router *1 - Power Adapter *1 - Ethernet Cable *1 - Quick Installation Guide *1	
Environment	- Operating Temperature: 0 ℃ ~40 ℃ (32 ˚F ~104 ˚F) - Storage Temperature: -40 ℃ ~70 ˚C (-40 ˚F ~158 ˚F) - Operating Humidity: 10%~90% non-condensing - Storage Humidity: 5%~90% non-condensing	